

510,551
10/510551

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
23 October 2003 (23.10.2003)


PCT

(10) International Publication Number
WO 03/086949 A2

- (51) International Patent Classification: **B67D**
- (21) International Application Number: PCT/US03/11056
- (22) International Filing Date: 11 April 2003 (11.04.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/372,123 12 April 2002 (12.04.2002) US
- (71) Applicant (for all designated States except US): **NORDSON CORPORATION** [US/US]; 28601 Clemens Road, Westlake, OH 44145 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **BOGER, Bentley, J.** [US/US]; 9225 Huntcliff Trace, Atlanta, GA 30350 (US).
SAINE, Joel, E. [US/US]; 625 Buckhorn Tavern Road, Dahlonega, GA 30533 (US).
- (74) Agents: **ROONEY, Kevin, G. et al.; WOOD, HERRON & EVANS, L.L.P.**, 2700 Carew Tower, Cincinnati, OH 45202 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: APPLICATOR AND NOZZLE FOR DISPENSING CONTROLLED PATTERNS OF LIQUID MATERIAL



(57) Abstract: An apparatus (10) for dispensing a filament of liquid includes a nozzle (12) having a liquid discharge passage (46) and a plurality of air discharge passages (70, 72, 74, 76). The liquid discharge passage (46) extends centrally through a frustoconical protrusion (89) which is located in a recess (88). The air discharge passages (70, 72, 74, 76) are arranged in a pattern around the liquid discharge passage (46) at the base of the protrusion (89) within the recess (88). The air discharge passages (70, 72, 74, 76) have axes (70a, 72a, 74a, 76a) which are inclined such that jets of air from the air discharge passages (70, 72, 74, 76) are tangential to the filament (13) dispensed from the liquid discharge passage (46). The jets of air cause the filament (13) to move in a swirl pattern as it is deposited on a substrate (18).

WO 03/086949 A2

WO 03/086949 A2



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.